

Swimming Pool Heater




Energy Efficient



COP 5 to 6.5



Heat Exchanger
Titanium Coil & PVC Shell



Design to suite
tropical conditions



Specification of Swimming Pool Heater

Advices Pool Volume m ³	15-25	40-60	80-100	120-140	150-180
Adviced Water circulation m ³	2.6	3.8	6.7	12	25
Operating Ambient Range	8 to 40°C	8 to 40°C	8 to 40°C	8 to 40°C	8 to 40°C
Noise Level (dB)	60	62	62	69	69
Power Supply	230	415	415	415	415
Input Power (kW)	1.8	2.7	4.5	7.8	15
Current (Amp)	6.7	5.5	9.2	16.0	30.7
Heat Exchanger	SS / Titanium	SS / Titanium	SS / Titanium	SS / Titanium	SS / Titanium
Outer Cabinet	MS Sheet Powder Coated	MS Sheet Powder Coated	MS Sheet Powder Coated	MS Sheet Powder Coated	MS Sheet Powder Coated
Water Connection Size in Inches BSP	3/4"	3/4	1	1 1/4	2
Physical Dimensions in mm.	600 X 600 X800H	600 X 600 X800H	700 X 700 X1200H	1200 X 1200 X1700H	2500 X 1200 X 1700
Net Weight	110	120	200	300	400



Plot No. 55, Gut No. 17, Paithan Road,
Georai Tanda, Aurangabad - 431002
Phone : 9422211126, 9225811126
Email : herambac@gmail.com
Web Site : www.airwaterheater.in

Dealer / Distributor :